

## **F** 50

## FORWARD VIBRATORY PLATE



## For compaction of sand, gravel and rock fill.

All our machine models are versatile and easy to operate. They are also durable and reliable, which means lower operating and maintenance costs.

- The Swepac F 50 is suitable for smaller jobs, such as adjusting the subsurface for paving bricks and stones.
- With a Vulkollan® plate (accessory) attached to the base, it can compact paved areas efficiently for an even surface.
- The machine can cope with the toughest of jobs since the entire machine protected is by a cover.
- The handle can easily be removed without any tools, and the machine can be transported in the trunk of a regular-sized car.
- The chassis and protection frame are hotdip galvanized providing a superior corrosion protection and maintenance-free life.

TECHNICAL DATA – <b>Swepac f 50</b>	
Weight, net	52 kg
Base plate, width x length	300 x 500 mm
Height, max / min	1010 / 700 mm
Length, max / min	1125 / 565 mm
Engine	Honda GXR 12
Fuel tank capacity	0.8 liter
Fuel	Unleaded or alkylate petrol
Engine output, max	2.3 kW (3.1 hp)
Centrifugal force	9 kN
Frequency	115 Hz
Working speed	0-25 m/min

Hand/arm vibrations HAV according to ISO 5349 on gravel surface	4.5 m/s <sup>2</sup>
Guaranteed sound-power level, LwA	105 dB(A)
Sound pressure level (at operator's ear), OP	89 dB(A)

PART NUMBER	
305050	F 50 with Honda petrol engine
ACCESSORIES	

305039 Vulkollan plate complete

F50\_2021-05\_GB